according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : AUTOL Meißelpaste, Art.-no. 1265

Revision date: 17.03.2015 **Version (Revision):** 4.0.0 (3.0.0)

Print date: 31.05.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

AUTOL Meißelpaste

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Lubricants, greases, release products (Fat).

Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Eni Schmiertechnik GmbH **Street:** Paradiesstr. 14

Postal code/city: D - 97080 Würzburg

Telephone: (+49) 931 900 98-0 **Telefax:** (+49) 931 98442 **Information contact:**

Technical Department, Tel. (+49) 931 900 98-145

technik.wuerzburg@agip.de

www.enischmiertechnik-datenblaetter.de

1.4 Emergency telephone number

1.3

SECTION 2: Hazards identification

The classification was made according to the latest editions of the EC-lists, and expanded upon from company and literature data.

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aquatic Acute 1; H400 - Hazardous to the aquatic environment: Category 1; Very toxic to aquatic life.

Aquatic Chronic 3; H412 - Hazardous to the aquatic environment: Category 3; Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms



Environment (GHS09)

Signal word

Warning

Hazard statements

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P391 Collect spillage.

2.3 Other hazards

None

SECTION 3: Composition / information on ingredients

Page: 1 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : AUTOL Meißelpaste, Art.-no. 1265

Revision date: 17.03.2015 **Version (Revision):** 4.0.0 (3.0.0)

Print date: 31.05.2015

3.2 Mixtures

Description

Base oil with thickener and additives.

Hazardous ingredients

COPPER; REACH registration No.: 01-2119480154-XX; EC No.: 231-159-6; CAS No.: 7440-50-8

Weight fraction: 2.5 - < 10 %

Classification 1272/2008 [CLP]: Aquatic Acute 1; H400 Aquatic Chronic 2; H411

DI-TERT-DODECYL POLYSULFIDE; EC No.: 270-335-7; CAS No.: 68425-15-0

Weight fraction: 1 - < 10 %

Classification 1272/2008 [CLP]: Aquatic Chronic 4; H413

CALCIUMDIALKYLBENZOLSULFONAT; EC No.: 298-637-4; CAS No.: 93820-57-6

Weight fraction: 1 - < 10 %

Classification 1272/2008 [CLP]: Skin Irrit. 2; H315 Aquatic Chronic 3; H412

Additional information

Full text of R-, H- and EUH-phrases: see section 16.

3.3 Additional information

For ingredients without any information about the EG-number we will use a generic name according to RL 1999/45/EG amendment VI. Highly refined mineral oil (IP 346 DMSO extract < 3%).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

In case of inhalation

No special measures are necessary. Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

In case of skin contact

After contact with skin, first remove product with a dry cloth and then wash the skin with plenty of water.

After eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Wash with plenty of water. Call a physician immediately.

After ingestion

Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray jet , Foam , Extinguishing powder , Carbon dioxide (CO2) , Sand . Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet .

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon dioxide (CO2), Nitrogen oxides (NOx). Sulphur dioxide (SO2). Carbon monoxide. Aliphatic and aromatic pyrolysis products.

5.3 Advice for firefighters

Special protective equipment for firefighters

Page: 2 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : AUTOL Meißelpaste, Art.-no. 1265

Revision date: 17.03.2015 **Version (Revision):** 4.0.0 (3.0.0)

Print date: 31.05.2015

Use suitable breathing apparatus.

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothes. Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

6.2 Environmental precautions

Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

Special danger of slipping by leaking/spilling product. Take up mechanically. Disposal: see section 13.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No hazardous reaction when handled and stored according to provisions. (Health hazards : None) . Avoid contact with skin, eyes and clothes.

Protective measures

Measures to prevent aerosol and dust generation

No special measures are necessary.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Dispose according to legislation.

Hints on joint storage

Possibility of hazardous reactions: Oxidising agent.

Storage class: 13

Storage class (TRGS 510): 11

Further information on storage conditions

Keep/Store only in original container. Notice the directions for use on the label.

Do not store at temperatures below : $0 \, ^{\circ}\text{C}$. Recommended storage temperature : $5 \, ^{\circ}\text{C}$ - $40 \, ^{\circ}\text{C}$.

Protect against: Protect against direct sunlight. Keep away from heat.

Storage stability : > 6 months (5 °C - 40 °C) .

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

Danger: Generation/formation of aerosols Limit value: 10 mg/m³.

8.1 Control parameters

Occupational exposure limit values

COPPER; CAS No.: 7440-50-8

Limit value type (country of origin): TRGS 900 (D)

Parameter: measured as the inhaleable fraction

Limit value: 1 mg/m³

Remark: DFG, E-STAUB ATEMBAR

Version:

Page: 3 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : AUTOL Meißelpaste, Art.-no. 1265

Revision date: 17.03.2015 **Version (Revision):** 4.0.0 (3.0.0)

Print date: 31.05.2015

8.2 Exposure controls

Appropriate engineering controls

See protective measures under point 7 and 8.

Personal protection equipment

General health and safety measures No special measures are necessary.

Eye/face protection

Additional eye protection measures: 39 - Wear eye/face protection.

Skin protection

Hand protection

Tested protective gloves must be worn Breakthrough time (maximum wearing time): 4 hours (NBR (Nitrile rubber), Thickness of the glove material: 0,4 mm). See information supplied by the manufacturer.

Respiratory protection

No special measures are necessary.

General health and safety measures

Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. 13 - Keep away from food, drink and animal feeding stuffs. Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Paste

Odour

characteristic

Safety relevant basis data

 Melting point/melting range:
 (1013 hPa)
 >
 250
 °C

 Boiling temperature/boiling range:
 (1013 hPa)
 >
 250
 °C

 Flash point:
 >
 250
 °C

 Danger of explosion:
 No explosive hazard

Density: (20 °C) ca. 0,96 g/cm³ DIN 51757

Not miscible or difficult to

Solubility in / Miscibility with Water:

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions (See section 7).

10.5 Incompatible materials

Oxidising agent, strong.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses. Decomposition temperature (°C): > 240 °C . Thermal decomposition can lead to the escape of irritating gases and vapours. Hazardous decomposition products: Carbon monoxide. Carbon dioxide (CO2). aldehydes.

Page: 4 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : AUTOL Meißelpaste, Art.-no. 1265

Revision date: 17.03.2015 **Version (Revision):** 4.0.0 (3.0.0)

Print date: 31.05.2015

Ketone, Sulphur oxides, Nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Irritant and corrosive effects

Repeated exposure may cause skin dryness or cracking. After eye contact: Irritation to eyes.

Primary irritation to the skin

Practical experience/human evidence

No hazardous reaction when handled and stored according to provisions. (Health hazards : None known.)

Sensitisation

No information available.

SECTION 12: Ecological information

Do not allow to enter into surface water or drains.

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Further ecological information

None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Waste treatment options

Appropriate disposal / Product

ASN 12 01 12: spent waxes and fats.

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Completely emptied packages can be recycled. Packing which cannot be properly cleaned must be disposed of. Handle contaminated packages in the same way as the substance itself.

Other disposal recommendations

Dispose according to legislation. Do not allow to enter into surface water or drains.

SECTION 14: Transport information

14.1 UN number

Land transport (ADR/RID): UN3077

Sea transport (IMDG): UN

Air transport (ICAO-TI / IATA-DGR): UN3077

Page: 5 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : AUTOL Meißelpaste, Art.-no. 1265

Revision date: 17.03.2015 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 31.05.2015

14.2 UN proper shipping name

Land transport (ADR/RID)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (COPPER)

Air transport (ICAO-TI / IATA-DGR)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., COPPER POWDER)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es): 9
Classification code: M7
Hazard identification number (Kemler No.)
: 90

Special provisions : LQ27 · E 1 **Hazard label(s) :** 9 / N

Air transport (ICAO-TI / IATA-DGR)

Class(es): 9
Special provisions: E 1
Hazard label(s): 9 / N

14.4 Packing group

Land transport (ADR/RID): III
Air transport (ICAO-TI / IATA-DGR): III

14.5 Environmental hazards

Land transport (ADR/RID): Yes

Air transport (ICAO-TI / IATA-DGR): Yes

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU legislation

Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP] .

National regulations

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.2. III): 4-5 %

Water hazard class (WGK)

Class: 1 (Slightly hazardous to water) Classification according to VwVwS

15.2 Chemical Safety Assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 03. Hazardous ingredients · 08. Occupational exposure limit values · 14. UN proper shipping name - Land transport (ADR/RID) · 14. UN proper shipping name - Air transport (ICAO-TI / IATA-DGR) · 14. Transport hazard class(es) - Land transport (ADR/RID) · 14. Transport hazard class(es) - Air transport (ICAO-TI / IATA-DGR) · 15. Water hazard class (WGK)

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

Page: 6 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : AUTOL Meißelpaste, Art.-no. 1265

Revision date: 17.03.2015 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 31.05.2015

None

16.4 Relevant H- and EUH-phrases (Number and full text)

H315 Causes skin irritation. H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

16.5 Training advice

None

16.6 Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 7 / 7